



## ISO Card MIFARE

<b>Description</b>	Configurable, flexible white-white ISO card with 1 kbytes data memory design to suit to most 13.56 MHz applications.		
<b>IC type:</b>	MIFARE Standard MF1 S50.		
<b>Physical:</b>	Thickness :	0.80 mm	± 0.06 mm
	Length:	85.60 mm	± 0.12 mm
	Width:	53.98 mm	± 0.05 mm
	Weight :	5.30 g	± 0.50 g
	Color :	White / white	
<b>Transport keys:</b>	KEY A FF FF FF FF FF FF KEY B FF FF FF FF FF FF		
<b>Printing:</b>	Both side are full printable with offset, thermo-transfer and dye sublimation printing.		
<b>Contact module:</b>	Customer may embed a contact module at ISO position.		
<b>Magnetic stripe:</b>	Optional HICO 2750 Oe magnetic stripe in ISO position.		
<b>Electrical::</b>	Operating Frequency:	13.56MHz	
<b>Material:</b>	PVC, white / white (Glossy).		
<b>Thermal:</b>	-35°C and +50 °C	(-30 °F and +122 °F)	according to <b>ISO 7816</b> .
<b>Resistance:</b>	The card is designed to resist common stress known from public transportation and crypto payments environments.		
<b>Parts number:</b>	W/O magn. Stripe: <b>607401</b> / 2750 Oe magn. Stripe: <b>607402</b>		